

TUBING SAFETY VALVES

Hi-Kalibre's line of high performance safety valves are used by the well service industry to prevent fluid loss and as a protection against well pressure fluctuations. Our unique design allows for positive sealing under load in gas environments, making these valves the superior choice for snubbing applications as well.



DESIGN FEATURES INCLUDE:

- Full drift
- Positive, gas tight sealing in both directions
- High torque body connection ensures seamless operation in the toughest conditions
- Low torque operation even when closing or opening under maximum bore pressure
- Gas tight stem seal even under maximum pull
- Full NACE compliant
- Available with a wide variety of sizes and end connections
- Reliable, field proven, serviceable design

Series	Top/Bottom Connection	ID/OD (")	Length (")	Pressure (psig)	Weight (lbs.)	Alternate End Connection/Configuration
0500-M-SERIES	2-3/8" EUE BOX 2-3/8" EUE PIN	2.00 4.25	20.00	5,000	39	
0725-MS-SERIES	2-3/8" EUE BOX 2-3/8" EUE PIN	2.00 3.85	19.75	5,000	38	
1075-SERIES	2-7/8" EUE BOX 2-7/8" EUE PIN	2.42 4.75	23.00	5,000	60	2-7/8" NUE, 3-1/2" EUE
1100-SERIES	2-7/8" EUE BOX 2-7/8" EUE PIN	2.43 5.30	24.00	5,000	76	2-7/8" IF BOX, 2-7/8" RTS6 10,000 WP
1200-TT390-SERIES	TT-390 BOX TT-390 PIN	2.69 5.90	32.00	10,000	132	
2075-SERIES	3-1/2" EUE BOX 3-1/2" EUE PIN	2.93 6.13	26.50	5,000	108	3-1/2" NUE
2100-SERIES	3-1/2" EUE BOX 3-1/2" EUE PIN	2.93 6.50	25.50	5,000	125	3-1/2" RTS6 10,000 WP, 3-1/2" HYDRIL W533 10000 PSI
2500-M-SERIES	4-1/2" EUE BOX 4-1/2" EUE BOX	4.00 8.00	27.00	5,000	213	4-1/2" NUE, 4-1/2" LTC
2600-SERIES	5-1/2" LTC BOX 5-1/2" LTC BOX	5.00 9.75	27.00	5,000	316	

Contact Hi-Kalibre Equipment for custom sizes or configurations.